SILVERBROOK RESEARCH Pty Ltd
393 Darling Street Balmain NSW 2041 Australia
PO Box 207 Balmain NSW 2041 Australia
Phone: +61 2 9818 6633 Patent Dept Fax: + 61 2 9555 7762
Email: patentdept@silverbrookresearch.com
ACN 066 573 671

18 September, 2008

United States Patent and Trademark Office
Commissioner for Patents
PO Box 1450
Alexandria 22313-1450 VA
United States of America

Attention: Certificates of Correction Branch

Dear Sir/Madam:

United States Patent No. 7,322,686 (10/534,804)
Inventors/Assignors: KIA SILVERBROOK
Assignee: SILVERBROOK RESEARCH PTY LTD
Docket No. MJT007NPUS

Please find attached form PTO/SB/44 requesting corrections to a typographic error in the claims set on the Patent Deed, for the above mentioned patent.

As these corrections do not result from errors caused by the applicants, no fee has been submitted.

Yours faithfully

Kia Silverbrook

Encl.

PTO/SB/44 (04-05)
Approved for use through 04/30/2007. OMB 0651-0033
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

(Also Form PTO-1050)

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7322686

APPLICATION NO.: 10/534804

ISSUE DATE : 29 January 2008

INVENTOR(S) : Kia Silverbrook

It is certified that an error appears or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 25, lines 4-8, Claim 1 should read: the at least one heater element is deposited in a plane parallel to both the planar support surface and the planar nozzle plate such that it forms a suspended beam positioned for immersion in the bubble forming liquid so as to be in thermal contact therewith.

Column 27, lines 20-27, Claim 17 should read:
at least one respective heater element corresponding to each nozzle aperture for thermal contact with a bubble forming liquid to heat at least part of the bubble forming liquid to a temperature above its boiling point to form a gas bubble therein thereby to cause the ejection of a drop of the bubble forming liquid through the nozzle aperture corresponding to that heater element; wherein, the at least one heater element is deposited in a plane

Column 28, lines 30-32, Claim 33 should read:
33. A method of ejecting a drop of an ejectable liquid from a printhead that has: a substrate having a planar support surface;

Column 28, lines 56-60, Claim 33 should read:

feeding bubble forming liquid to immerse each of the heater elements and feeding ejectable liquid to the nozzle plate to be retained adjacent the nozzle apertures;

Kia Silverbrook
Managing Director
Silverbrook Research Pty Ltd

MAILING ADDRESS OF SENDER (Please do not use customer number below):

Mr Kia Silverbrook
Silverbrook research Pty Ltd
393 Darling Street, Balmain NSW 2041, Australia